

PEEL AWAY 8

PAINT REMOVAL SYSTEM

GUIDE FOR USING: PEEL AWAY EIGHT

- **Removes up to 15 layers of paint in one application**
- **Safe lead paint removal**
- **No toxic fumes**
- **Less labour intensive**
- **Preserves most substrates**
- **Removes multiple coats of architectural and tough industrial coatings from virtually all surfaces.**

Suitable for use on surfaces such as:

Virtually all exterior and internal surfaces – wood, brick, metal, concrete, painted aluminium, stone, plaster, painted fibreglass etc. Peel Away 8 does not scorch (darken) timber. As all situations vary, always perform a test patch evaluation.

Works on oil, varnish and acrylic paints and some polyurethane coatings.

Not suitable for use on surfaces such as:

VENEERS, PLYWOODS and COMPOSITION surfaces or for BAKED ENAMELS, some 2 PART EPOXIES and URETHANES. Do not use on unpainted fibreglass.

PEEL AWAY is a thick paste that is applied to unwanted paint coatings then covered with the PEEL AWAY Laminated Cover. Simply leave and then PEEL AWAY with the aid of the spatula supplied.

Packaging: PEEL AWAY 8

- 300g Includes ¼ Laminated paper cover & 1 spatula
- 1kg Includes 1 Laminated paper Cover and 1 spatula
- 5kg Includes 3 Laminated paper Covers and 1 spatula (coverage 3sqm)
- 15kg Includes 10 Laminated paper Covers and 1 spatula (coverage 10sqm)
- 225kg Includes 120 Laminated paper Covers (coverage 120 sqm)

Coverage:

As a guideline, an application rate of **3mm thickness** would require 1.5 kg for 1sq.m. (Approximate only)

Tools you need to complete a successful job:

- Only use PEEL AWAY Laminated Paper Covers
- Available water supply, a nylon brush, trowel or spatula supplied.
- Long thick rubber gloves and overalls
- Eye protection goggles, masking tape, scissors or knife
- Plastic drop sheets for protection of surrounding surfaces

Extra Laminated Paper Cover Sheets may be required, because paste coverage may go further.

Supplied with this pack:

- PEEL AWAY 8 paste
- Comprehensive instruction and safety sheet
- Spatula and Laminated Paper Covers

DIRECTIONS FOR USE:

1. Test Patch – ALWAYS PERFORM A TEST PATCH BEFORE EVERY JOB!

Test patch evaluation should always be completed before undertaking any paint removal project as all paint systems and surfaces vary. 300g Trial pots and 1kg sizes are available for test purposes.

2. Application

- i) Apply PEEL AWAY 8 using a nylon brush, trowel or spatula. Application rate varies according to age, type and thickness of coatings. Note: An application rate of 3mm thick is satisfactory in most cases, however, up to 6mm thickness may be required for very thick exterior paint systems.
- ii) Cover paste with PEEL AWAY Laminated Paper Cover, printed side out. Rub gently to remove air bubbles. Pierce air bubbles with a pin. On external surfaces always seal edges of Laminated Paper Cover with masking tape for optimal results **(Only use Peel Away Laminated Paper Cover)**.
- iii) Allow to stand for 6 to 72 hrs. PEEL AWAY 8 softens layer upon layer of paint and when it is ready to remove, it generally turns a light to dark brown colour. Generally do not leave for more than 72 hours, as drying may cause difficulty in removal and/or could affect the surface pH level. Check at regular intervals. **Note:** On very porous surfaces, remove PEEL AWAY 8 as soon as the Laminated Paper Cover starts to turn light to dark brown.

3. Removal and Cleaning

- i) For ease of removal it is recommended to cut the sheet into smaller sections with a knife.
- ii) For each section, slide spatula behind laminated Cover and gently lift Laminated Paper Cover with paint and paste. If paste is slightly dry when removing due to high temp– mist wet with water and remove.
- iii) For best results, immediately wash each section thoroughly with water, nylon brush and sponge. For any remaining spots of paint not removed, further apply a thin layer of PEEL AWAY 8, 1/2 hour to 1 hour without paper, then remove.

SAFETY DIRECTIONS:

Warning: Peel Away 8 is a safe solvent based product. It is formulated without toxic chemicals and will not burn skin. **In case of contact with skin or eyes, wash well with water.**

Protective equipment

- i) Wear long rubber gloves taped to sleeves to prevent PEEL AWAY 8 from contacting skin.
- ii) Where prolonged use is anticipated, apply barrier cream to hands and arms. **Wear eye or face protection when stripping paint off ceilings at all times.** Protect any surface not to be stripped with polyethylene /plastic or protection boards and mask edges. Dispose of contaminated waste, solid or liquid form, in compliance with local regulations. Call EPA on 131555.

FIRST AID

If poisoning occurs, contact a Doctor or the Poison Information Centre.

If swallowed, do not induce vomiting. Give a glass of water.

If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

If in eyes, hold eyes open, flood with water for at least 15 minutes and see a Doctor.

Disposal

For household and small quantities, the EPA recommends placing containment into thick plastic bags and then disposal through the council garbage collection. For large quantities and all commercial waste disposal refer to strict local EPA guidelines. Refer Contractor Guide for more details.

Technical: The information is of general nature and every care is taken in preparation. No responsibility, nor warranty is expressed or implied for the suitability of the material as actual site conditions are all different.

Marketed and licensed to:

BLDCARE AUSTRALIA Pty Ltd ABN 87 003 914 038

Trading as PEEL AWAY AUSTRALIA –

ASIA PACIFIC PTY LTD

Unit 43 Homebush Business Village

11-21 Underwood Rd, Homebush NSW 2140

Phone: 02 9746 6733 Fax: 02 9746 5322

PEEL AWAY is a registered trademark and patented paint removal system.

Manufactured under licence by:

HAYMES PAINT PTY LTD

Waringa Drive, Wendouree Industrial Park

BALLARAT VICTORIA 3355

Phone: 1800 033 431

PEEL AWAY[®]
PAINT REMOVAL SYSTEM