

## **Compare EzyJamb Door Jamb Profiles**



EzyJamb is the flush door jamb system that eliminates the need architraves around the door frame and blends seamlessly into any modern square set interior design.

EzyJamb is available in three flush profiles to suit a variety of applications:







## All EzyJamb profiles:

- Are manufactured by Studco Building Systems, using high quality BlueScope cold-formed steel.
- Have perforated sides for flush jointing around the plasterboard, making them the fastest, most economical way to create flush door frames.
- Are specialty coated and meet the finished surfaces standard AS/NZS 2311:2009 to ensure they can be painted immediately.
- Have surpassed the 10,000 door slam test, proving their durability.
- Are available with premium RocYork concealed, herline or lift off hinges.

With three EzyJamb profiles to choose from, we have outlined a few key differences on the next page that will help you to choose the right product for your project.

Alternatively, you can contact us on 1300 399 526 for assistance.



## **Compare EzyJamb Door Jamb Profiles**



Product Code	EzyJamb EZC – Classic Adjust Door Jamb	EzyJamb SRC – Single Rebate Door Jamb	EzyJamb ISD – Inswing Door Jamb
Description	Two-piece adjustable split type door jamb – flush on one side of the door and rebated on the other.	One-piece door jamb – flush on one side of the door, with a single rebate on the other.	The door swings open into the corresponding room, with the flush side in line with the wall face. Perfect for hallways and corridors.
Product Image			
Suitable for internal door applications	Yes	Yes	Yes
Two-piece adjustable jamb (10mm +/-)	Yes		
One-piece jamb		Yes	Yes
Rebate on 'push' side of the door	Classic rebate	Single Rebate	Flush with wall face
Rebate on 'pull' side of the door	Flush with wall face	Flush with wall face	Single rebate
Made from BlueScope Zincanneal Steel	Yes	Yes	Yes
Door Height	2040mm or 2340mm	2040mm - 2340mm	2040mm - 2340mm
Door Width	420mm – 1020mm	420mm – 1020mm	420mm – 1020mm
Finished Wall Thickness	82mm – 220mm	80mm – 220mm	80mm – 220mm
Custom Sizes Available on Request	Yes	Yes	Yes
Selected sizes available for QuickShip.	Yes	Yes	
Suitable Door Thickness	35mm, 38mm & 45mm	32mm – 60mm	Minimum 45mm
Concealed Hinges	Yes	Yes	Yes
Herline Hinges	Yes	Yes	
Lift Off Hinges	Yes	Yes	
Mortice Butt Hinges			Yes
Door Handing	OUTED OUTE Notice Notic	OUTSIDE NESTOR OUTSIDE NESTOR STATE OF THE NESTOR OUTSIDE Right Hand Reverse Opening	Left Nand Roverse Opening  Bight Hand Roverse Opening  OUTSIDE  OUTSIDE  NOTICE  NOTICE

nformation contained within this document supersedes all previous versions and is subject to change without notice