





GEORGIAN



To view colour swatches for each state refer to www.monier.com.au

With its fine textured surface and flat profile, Georgian roof tiles recall the precise edges of colonial sawn timber shingles.



TILES USAGE WITH WASTAGE (+/-2%)
Approx. 11.6 tiles per sqm.

TILE COVERAGE (±2%)
Approx. 10.0 tiles per sqm.

DIMENSIONS (±2%)
Length 415mm
Width 329mm

MASS (±2%)
Per tile 5.20kg
Per m² 52.0kg

HEAD LAP ADJUSTMENT (MM)
80* – 100 (*With the use of sarking)

FEATURE
Flat with lines

COLOUR APPLICATION
Colour Through

RECOMMENDED BONDING
Cross bond

ROOF PITCH
Minimum Pitch with Sarking: 15°
Minimum Pitch without Sarking: N/A



Please consult the Design Guide at Monier.com.au for installation requirements applicable to your project.

Please refer to AS2049 for acceptable tolerance to these measurements stated above.



CONCRETE ACCESSORIES

ACCESSORY	LENGTH (MM)	WIDTH (MM)	HEIGHT (MM)	ANGLE (DEGREE)	WEIGHT (KG)
Parbarge 	420	248	126	84	4.9
Starter 	420	250	80	120	2.8
3-Way Apex (butt & overlapping) 	391.7	413.3	135	135	3.8
Ridge 	420	250	80	120	3.4
Ridge Saddle 	205	250	175	120	3.3
Gable Finial — Scroll 	245	240	280	120	5.1
Apex Finial — Scroll 	385	420	320	120	6
Spoon-Starter 	410	395	125	120	6