

POLYSAFE VERONA PUR



2.0mm



2m x 20m = 40m<sup>2</sup>



2600g/m<sup>2</sup>



**GENERAL PERFORMANCE**

EN 13845  
ASTM F1303



**REACTION TO FIRE**  
EN 13501-1 Class Bfl-S1  
ASTM E648 Class 1



**ABRASION RESISTANCE**  
EN 13845 50,000 cycles  
EN 649 Group T



**ENHANCED SLIP**

**Sustainable wet slip resistance\***  
EN 13845 ESf

AS/NZS 4586 R10

RRL Pendulum Test  $\geq 36$  (wet test - 4S Rubber/Slider 96)

Surface roughness Rz  $\geq 20\mu\text{m}$

The slip resistance across all Polysafe products is assured throughout the guaranteed life of the product, with strict adherence to HSE Guidelines.



**VOC EMISSIONS**  
AgBB/DiBT : Pass  
FloorScore certified



**AGRÉMENT ASSURANCE**

Independently assessed by the BBA and awarded a 10 year product performance assurance in recommended use areas.



**ENVIRONMENTALLY PREFERABLE FLOORING**

Polysafe Verona PUR achieves BRE Global Environmental Generic A+ rating in major use areas such as education and healthcare. Generic EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains recycled material. Recyclable via the Recofloor scheme. Visit [www.polyflor.com/environment](http://www.polyflor.com/environment)



**HYGIENE**

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



**ELECTRICAL BEHAVIOUR**

(body voltage)

EN 1815  $\leq 2\text{kV}$

Classified as 'antistatic'



Polysafe Verona PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention. As with all Polysafe products, Polysafe Verona PUR should not have a polish applied.



**APPLICATIONS**

Polysafe Verona PUR is ideal for use in areas where contaminant spillages can occur, making slip resistance an important consideration. Typical areas include circulation areas and corridors, dining areas and cafes, classrooms, hospital wards, clinics, laundry and sluice rooms, nursing homes, washrooms, WCs, bar serveries, food preparation areas, kitchens, canteens and institutional applications. For continually wet areas please refer to our Polysafe Hydro, Hydro Evolve or Ultima ranges.



Polysafe safety flooring ranges have good resistance to dilute acids and alkalis, are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. Chemical resistance charts available on request. For clarification and for information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com). At the date of issue the data presented is correct. However, Polyflor Ltd. reserves the right to make changes which do not adversely affect performance or quality.

\* For clarification regarding slip resistance, consult Polyflor.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551  
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912  
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128  
EXPORT FAX: +44 (0)161 767 1166  
E-MAIL: [INFO@POLYFLOR.COM](mailto:INFO@POLYFLOR.COM) [WWW.POLYFLOR.COM](http://WWW.POLYFLOR.COM)

James Halstead  
FLOORING



2011



Recofloor™  
Vinyl Take-Back Scheme



Polysafe™  
Verona

Advanced design with safety assured



PERFORMANCE AND PROPERTIES



Refer to BRE Global ratings on [www.greenbooklive.com](http://www.greenbooklive.com)



In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainable construction via Environmental Product Declarations (EPDs).

