

DESIGN DEPARTMENT - PRODUCT SPECIFICATION SHEET

DATE: 18.6.19

DESIGN NAME:		EchoPanel [®] Inline
DESIGNER:		Woven Image
ORIGIN:		Australia/China
COLOURS:		548, 340, 366
PANEL DIMENSION:		1150 mm x 890 mm +/- 2 mm
PRINT DIMENSION:		1074 mm x 814 mm +/- 2 mm
PANEL THICKNESS:		24 mm +/- 7%
CABLE LENGTH:		2000mm
WEIGHT:		10 kg per kit
KIT CONTENTS:		3 x Cut & Printed EchoPanel® pieces 12 x Ceiling Mount (stainless steel) 12 x Cable (stainless steel) 24 x Panel fixtures + fixture covers 12 x Adjustable cable stoppers 72 x Self-tapping screws 1 x Installation guide.
12 X Ceiling mounts	12 X Steel cables	
Ì	\bigcirc	890
24 X Panel fixtures	24 X Panel fixture covers	
	-	38 1074 38
e e	Amme	3 X Printed Panles
12 X Adjustable cable stoppers	72X Self-tapping screws	

For more information phone +61 2 9913 8668 or 1800 888 650 or visit www.wovenimage.com



PERFORMANCE COLOUR FASTNESS TO LIGHT: ISO 105-B02-1994 Rating: 6-7 FIRE TEST: ISO 9705: Group 1 ASTM E84 Unadhered: Class 2 or B BS EN 13501.1: Classification B-s1, d0 CARE: Blot excess spills from material quickly. Wipe with a damp cloth. If stain persists, apply small quantities of carpet or upholstery shampoo solution with a damp cloth. Blot well with a clean cloth after each application of the solution. Warning, avoid excessive amounts of water. Ensure adequate ventilation if the product is likely to be subject to excessive moisture. SOUND ABSORPTION: Weighted sound absorption coefficient as defined by ISO 11654 standard (200mm suspension):0.50(H) Sound Absorption Average as defined by ASTM C423 (200mm suspension): 0.51 VOC EMMISSIONS: ASTM D5116 Rate: < 0.02 mg/m²/hr (7 days) VO **ENVIRONMENTAL:** EchoPanel[®] achieves GreenTag Certification GreenRate: Level A

OVERALL ASSEMBLY

