

Product Data Sheet



DesignLite

Type/Item No: **FLEDIP**



Features:

Flexible IP65 LED strip. High output 5050 SMD LED Designed for installation onto various surfaces. Indoor and outdoor application flexible with a maximum bend diameter of 4cm. The standard length of 5 meters using 12v DC can be cut for smaller installations. Fixing is by 3M double sided adhesive backing. The width of the flexible strip 10mm with a viewing angle of 120deg. Making this flexible LED strip widely acceptable for many difficult situations. The accessories are sold separately. A separate 12v driver is required to power the flexible LED strip. 5 metre reel consists of 60LED per metre @ 14.4W per metre @ 0.6A per metre. Therefore 5 metre reel is 72w
Optional: Remote control non weatherproof LED dimmer is available for added lighting management



Class:	IP	Colour:
1	65	

Lamp:

5050 SMD Top LED (3 chip)

Gear:

Remote constant voltage 12v DC LED power supply sold separately

DRV100IP	100w
DRV150IP	150w

FLEDIP-W
FLEDIP-WW
FLEDIP-B
FLEDIP-R
FLEDIP-Y
FLEDIP-G

White	660lm	per mt
Warm White	540lm	per mt
Blue	80lm	per mt
Red	230lm	per mt
Yellow	180lm	per mt
Green	390lm	per mt

DRV150IP
DRV100IP

150w IP Power Supply Suit 10metres
100w IP Power Supply Suit 5metres

LED-Dimmer

Remote control 12v DC rated @ 18A
(Not weatherproof)

Dimensions:

