

WE'VE GOT YOUR FLOORS COVERED

FROM TOP TO BOTTOM.

Set a Solid Foundation with Dunlop's Hard Flooring Underlay for Timber, Laminate and Vinyl Floors.

All of Dunlop's Hard Flooring Underlays provide superior acoustic performance and the required moisture protection, so as to meet the needs of the Australian market, the *European Producers of Laminate Flooring (EPLF)* and the *North American Laminate Flooring Association (NALFA)* guidelines.

 **Timbermate**

2mm

Dunlop Timbermate is a hard flooring underlay specially designed to reduce sound transfer whilst also providing added moisture protection.

Water Vapour
Transmission

86 S_d

Acoustic Rating*

58dB

 **Thermoacoustic**

3mm

Dunlop Thermoacoustic is a hard flooring underlay specially designed to offer an increased reduction in sound transfer whilst also providing added moisture and thermal protection.

174 S_d

55dB

 **TIMBERCUSHION**

2mm

Dunlop Timbercushion is a specialist hard flooring underlay that provides superior acoustic performance. Incorporating a 200 micron moisture resistant barrier, Timbercushion offers effective moisture and thermal protection. This product includes an incorporated tape seal on the end of the rolls for increased water vapour resistance.

202 S_d

48dB

 **AQUACUSTIC**

3mm

Dunlop Aquacoustic is a specialist hard flooring underlay that provides unsurpassed acoustic performance. Incorporating a 200 micron moisture resistant barrier, Aquacoustic offers superior moisture protection. This product includes an incorporated tape seal on the end of the rolls for increased water vapour resistance.

203 S_d

47dB

 **Advantage 3**
COMFORT THAT LASTS

3mm

Dunlop Advantage 3 is a Rubber/Cork acoustic underlay suitable for conventional and double bond applications for wood, laminate and vinyl floors.

196 S_d**

46dB

Please Note: Bare Slab L_{n,w} result was 68 dB. Testing was conducted in accordance with standard **ISO 140-6**, over a 150mm reinforced concrete subfloor laid in combination with a timber floor. **Ceiling:** 13mm plasterboard on resiliently mounted furring channels with 75mm thick, 14kg/m³ fibrous insulation to cavity.

**To achieve the rating of 196S_d, for Dunlop Advantage 3, the product must be installed with a 200 micron plastic sheet.

For more information visit dunlopflooring.com.au

 **DUNLOP**® flooring
COMFORT THAT LASTS™