




# NOUVEAU



To view colour swatches for each state refer to [www.monier.com.au](http://www.monier.com.au)

Integrating beautifully with the design features of your home, Nouveau offers a streamlined, ultra-modern appearance with a unique satin finish that provides durability with excellent depth and intensity of colour.



**TILES USAGE WITH WASTAGE (+/-2%)**  
Approx. 13.0 tiles per sqm.

**TILE COVERAGE (±2%)**  
Approx. 12.6 tiles per sqm.

**DIMENSIONS (±2%)**  
Length 445mm  
Width 270mm

**MASS (±2%)**  
Per tile 3.80kg  
Per m<sup>2</sup> 47.9kg

**HEAD LAP ADJUSTMENT (MM)**  
Up to 110

**FEATURE**  
Modern

**COLOUR APPLICATION**  
Natural/Glazed

**RECOMMENDED BONDING**  
Cross bond

**ROOF PITCH**  
Minimum Pitch with Sarking: 15°  
Minimum Pitch without Sarking: 20°



Please consult the Design Guide at [Monier.com.au](http://Monier.com.au) for installation requirements applicable to your project.

Please refer to AS2049 for acceptable tolerance to these measurements stated above.



# CONCRETE ACCESSORIES

ACCESSORY	LENGTH (MM)	WIDTH (MM)	HEIGHT (MM)	ANGLE (DEGREE)	WEIGHT (KG)
<b>Parbarge</b> 	420	248	126	84	4.9
<b>Starter</b> 	420	250	80	120	2.8
<b>3-Way Apex (butt &amp; overlapping)</b> 	391.7	413.3	135	135	3.8
<b>Ridge</b> 	420	250	80	120	3.4
<b>Ridge Saddle</b> 	205	250	175	120	3.3
<b>Gable Finial — Scroll</b> 	245	240	280	120	5.1
<b>Apex Finial — Scroll</b> 	385	420	320	120	6
<b>Spoon-Starter</b> 	410	395	125	120	6