

# LEDFLOOD



Type/Item No: LEDF50

## Features:

- Die-cast aluminium alloy body
- Adjustable trunnion mounting bracket
- Stainless steel fixings
- Tempered clear glass (5mm)
- Silicone rubber seals
- Stainless steel cable gland
- Includes 1 x 50w LED driver
- 6500K colour temperature
- 240v direct connection
- Wide Beam Angle 120Deg
- Energy efficient alternative to halogen
- Low operating Temperature
- Less carbon emissions
- 50,000 hours
- No ultraviolet emissions
- 12 month warranty
- Weight 5KG



<b>Class:</b>	<b>IP</b>	<b>Colour:</b>
1	IP65	Grey

## Lamp:

1 x 50w single chip LED

## Gear:

Integral within housing at rear  
COMPLIANCES:

SAA approval: SAA120680EA  
EMC compliant

## LED Characteristics

Luminous Flux	3700lm
Luminous Efficacy	67 lm/w
Input Power	51w
Colour temperature	6500K
CRI	60Ra
Power factor	0.96
Line current	.525A

## Application:

Floodlighting and wall washing for Bars, Clubs, Hotels, Stages, Parks, Plaza, Commercial building façade, Domestic backyards, Parking Bays, Security areas, Walkways.

## Dimensions:

